





**MG SERIES****WATERPROOF VENTILATED CABLE GLAND****IP68, PA66, Temp:-40~120C****RoHS****Airflow: >20cc/min@7kpa****Datasheet**

Outline	Thread Spec.	Milvent P/N Black(B)	For Cable OD	Thread OD	Thread Length	Wrench OD	Packing
		Grey(G)	mm	C1 mm	C2 mm	A & F m m	pcs
<b>B</b> TYPE 	M8*1.25	MG8B-04	2.5 ~ 4.5	8	7.5	12/13.	50
		MG8B-02	1 ~ 2.5	8	7.5	12/13.	50
	M10*1.5	MG10B-06	2 ~ 6	10	8	14/15	50
		MG10B-03	1.5 ~ 3	10	8	14/15	50
	M12*1.5	MG12B-08	3.5 ~ 8	12	9	18/19	50
		MG12BS-07	2.5 ~ 6.5	12	7.5	15/18	50
		MG12BL-08	3.5 ~ 8	12	15	18/19	50
		MG12SL-07	2.5 ~ 6.5	12	15	15/18	50
	M16*1.5	MG16B-06	3.5 ~ 6.5	16	10	22/22	50
		MG16B-10	6.5 ~ 10	16	10	22/22	50
		MG16BS-08	3.5 ~ 8	16	8.5	19/22	50
		MG16SL-08	3.5 ~ 8	16	15	19/22	50
		MG16BL-06	4 ~ 7	16	15	22/22	50
		MG16BL-10	6 ~ 11	16	15	22/22	50
	M18*1.5	MG18B-10	6 ~ 10	18	10	22/24	50
		MG18B-06	4 ~ 7	18	10	22/24	50
		MG18BL-10	6 ~ 10	18	15	22/24	50
		MG18BL-06	4 ~ 7	18	15	22/24	50
	M20*1.5	MG20B-14	7.5 ~ 14	20	11	27/27	50
		MG20B-10	5 ~ 10	20	11	27/27	50
		MG20B-10.5	6 ~ 10.5	20	11	27/27	50
		MG20BL-14	7.5 ~ 14	20	15	27/27	50
		MG20BL-10	6 ~ 10	20	15	27/27	50
		MG20BL-10.5	5 ~ 10	20	15	27/27	50
		MG20BS-08	5 ~ 8.5	20	10	24/27	50
		MG20BS-12	6 ~ 12	20	10	24/27	50
		MG20BSL-12	6 ~ 12	20	15	24/27	50
		MG20BSL-08	5 ~ 8.5	20	15	24/27	50
		MG22B-14	7.5 ~ 14	22	10	29/27	50
		MG22B-10	5 ~ 10	22	10	29/27	50
	M25*1.5	MG25B-18	10 ~ 18.5	25	12	33/33	50
		MG25B-13	7 ~ 13	25	12	33/33	50
		MG25B-08	5 ~ 7.9	25	12	33/33	50
		MG25BL-18	12 ~ 18.5	25	15	33/33	50
		MG25BL-13	7 ~ 13	25	15	33/33	50
		MG25BL-08	5 ~ 7.9	25	15	33/33	50
		MG25BS-14	8 ~ 14	25	11	27/33	50
		MG25BS-10	5 ~ 10	25	11	27/33	50
		MG25BS-10.5	6 ~ 10.5	25	11	27/33	50
		MG32B-25	17 ~ 25	32	15	41/42	20
	M32*1.5	MG32B-12	8 ~ 12	32	15	41/42	20
	M36*1.5	MG36B-25	16.5 ~ 25	36	12	41/45	10
	M40*1.5	MG40B-30	20 ~ 30	40	15	50/52	10
		MG40B-25	21 ~ 26.5	40	15	50/52	10
	M50*1.5	MG50B-39	31 ~ 41	50	20	62/62	10
		MG50B-32	24 ~ 32	50	20	62/62	10
	M63*1.5	MG63B-49	44 ~ 51	63	20	75/76	10
		MG63B-46	34.5/46	63	18	75/76	10

Outline	Thread Spec.	Milvent P/N Black(B)	For Cable OD	Thread OD	Thread Length	Wrench OD	Packing
		Grey(G)	mm	C1 mm	C2 mm	A & F m m	pcs
<b>A</b> TYPE 	M12*1.5	M12A-08	4.5 ~ 7.8	12	8.5	18/19	50
		MG12A-05	3 ~ 5.3	12	8.5	18/19	50
		MG12A-065	3 ~ 6.5	12	8.5	18/19	50
	M16*1.5	MG12A-067	3 ~ 6.7	12	8.5	18/19	50
		MG16A-10	6 ~ 10	16	15	22/22	50
		MG16A-06	4 ~ 7	16	15	22/22	50
		MG16AS-08	4 ~ 8	16	10	22/19	50
		MG16A-10-ST	6 ~ 10	16	10	22/22	50
	M20*1.5	MG16A-06-ST	4 ~ 7	16	10	22/22	50
		MG20AS-12	6 ~ 12	20	10	27/24	50
		MG20AS-08	4 ~ 8	20	10	27/24	50
		MG20A-14	7 ~ 14	20	15	25/25	50
	M22*1.5	MG20A-10	7 ~ 11	20	15	25/25	50
		MG22A-14	7 ~ 14	22	15	25/25	50
	M25*1.5	MG22A-10	7 ~ 11	22	15	25/25	50
		MG25A-18	13 ~ 18	25	15	33/33	50
	M32*1.5	MG25A-16	10 ~ 16	25	15	33/33	50
		MG32A-25	17 ~ 25	32	15	41/42	20
	M40*1.5	MG32A-22	17 ~ 22	32	15	41/42	20
		MG40A-30	21 ~ 30	40	20	50/52	10
	M50*1.5	MG40A-25	21 ~ 25	40	20	50/52	10
		MG50A-39	30 ~ 41	50	22	62/62	10
	M63*1.5	MG50A-32	27 ~ 32	50	22	62/62	10
		MG63A-49	44 ~ 51	63	25	75/78	10
	M75*2	MG63A-46	40 ~ 46	63	25	75/78	10
		MG75A-66	56 ~ 66	75	25	92/92	2
	M90*2	MG75A-56	50 ~ 56	75	25	92/92	2
		MG90A-77	70 ~ 80	90	25	110/110	2
		MG90A-68	58 ~ 68	90	25	110/110	2